
























































































product name	basis weight (g/m ²)	thickness (µm)	sensitivity	preservability (years)	topcoated	recommended application	
JTK Extra Durable							
AP50KJ-R	55	63	••	25		 	
AP62KJ-R	75	83	••	25		    	
AP85KJ-R	115	110	••	25		  	
AP11KJ-R	140	150	••	25		 	
AP15KJ-R	170	180	••	25		 	
AP18KJ-R	205	210	••	25		 	
AP20KJ-R	235	250	••	25		 	
AP62KM-ID	75	83	••	20		    	
JTK Durable Topcoated							
AL54KT-S	60	66	••	12	TC		
AL60KT-S	72	79	••	12	TC	 	
AL60KT-M	72	79	•••	12	TC	   	
AL60KT-ML	76	83	•••	12	TC		NEW!
AL60KT-P	76	83	•••	12	TC		NEW!
AL60KT-PB	76	83	•••	12	TC		NEW!
AL60KT-N	76	83	•••	10	TC		NEW! NON PHENOL
AP63KT-M	78	85	•••	12	TC	 	
AP85KT-M	115	110	•••	12	TC	  	
AP11KT-M	140	150	•••	12	TC	  	
AP15KT-M	170	180	•••	12	TC	  	
AP18KT-M	205	210	•••	12	TC	  	
AP20KT-M	235	250	•••	12	TC	  	
JTK Durable							
AP45KS-FZ	48	55	••	10			
AP50KS-FZ	55	63	••	10		  	
AP62KS-FZ	75	83	••	10		    	
AP45KS-NP	48	55	••	10			NEW! NON PHENOL
AP50KS-NP	55	62	••	10		  	NEW! NON PHENOL
AP58KS-NP	71	79	••	10		    	NEW! NON PHENOL
AP62KS-NP	75	83	••	10		    	NEW! NON PHENOL
AP58KM-NL	71	79	•	10			NEW! NON PHENOL
AP62KM-I	75	83	•	10		  	

-  Medical charts
-  Parking tickets
-  Tags

-  Gaming tickets
-  Transportation tickets
-  Entrance tickets

-  Labels
-  POS, ATM
-  Bank statements, invoices

product name	basis weight (g/m ²)	thickness (µm)	sensitivity	preservability (years)	topcoated	recommended application	
JTK Standard	AP45KS-D	48	55	••	5		
	AP50KS-D	55	62	••	5		
	AF50KS-E	55	63	••	7		
	AP50KS-FD	55	62	••	10		NEW!
	AF50KS-E3	55	63	•••	7		
	AP50KM-A	55	63	•	5		
	AP50CM-A	55	63	••	5		
	AP50KS-DX	58	66	••	5		
	AF50KS-ET	62	68	••	7		
	AP58KM-A	71	79	•	5		
	AP58KM-IE	71	79	•	7		NEW!
	AP62KS-E	75	83	••	7		
	AP62KM-A	75	83	•	5		
	AP77KM-A	87	97	•	5		
	AP85KM-A	115	110	•	5		
	AP11KM-A	140	150	•	5		
	AP15KM-A	170	180	•	5		
	AP18KM-A	205	210	•	5		
	AP20KM-A	235	250	•	5		

- Medical charts
- Parking tickets
- Tags

- Gaming tickets
- Transportation tickets
- Entrance tickets

- Labels
- POS, ATM
- Bank statements, invoices